

CASE
CONSTRUCTION



F SERIES WHEEL LOADERS
1021F | 1121F



1021F	Z-Bar	XR
Maximum Net HP	296 hp (221 kW)	296 hp (221 kW)
Operating Weight	53,500 lb (24 267 kg)	55,781 lb (25 301 kg)
Bucket Capacity	5.5 yd ³ (4.2 m ³)	5.5 yd ³ (4.2 m ³)
Breakout Force	45,097 lbf (200.6 kN)	45,300 lbf (201.5 kN)
Hinge Pin Height	167 in (4244 mm)	188 in (4775 mm)
1121F	Z-Bar	XR
Maximum Net HP	320 hp (239 kW)	320 hp (239 kW)
Operating Weight	60,800 lb (27 578 kg)	62,608 lb (28 398 kg)
Bucket Capacity	6.25 yd ³ (4.8 m ³)	6.25 yd ³ (4.8 m ³)
Breakout Force	50,076 lbf (222.7 kN)	50,388 lbf (224.1 kN)
Hinge Pin Height	175 in (4445 mm)	190 in (4826 mm)



More power. Less fuel. Engineered for the toughest high-production aggregate and quarry applications.

New, high-performance machines

Case Construction Equipment expands its F Series wheel loader product line with two all-new models, the 1021F and 1121F. They are engineered for the toughest quarry, aggregate and truck-loading applications.

These new wheel loaders feature all of the Case product characteristics that customers demand: superior productivity, fuel efficiency, operator comfort and easy maintainability.

- Four power modes - Economy, Standard, Max and Auto - give operators flexibility to match engine power to their jobs.

- Case optimized stability for the 1021F and 1121F with a longer wheel base and lower center of gravity.
- Upgraded axles include a standard axle-cooling system and an optional hydraulically-locking front differential.
- A standard idle-management feature maximizes fuel economy and allows owners to meet local idle-reduction regulations.
- A new rear-view, wide-angle camera provides live video to a color monitor in the cab. (Optional)
- Joystick steering is available.
- Standard Z-bar and extended reach (XR) versions are available.
- Both models feature a full raise-up hood, environmentally safe fluid drains, sight gauges and grouped, ground-level checkpoints for easy maintenance.



CNH INTERNATIONAL SA
Riva Paradiso, 14
6902 Paradiso
SWITZERLAND



NOTE: Standard and optional fittings can vary according to the demands and specific regulations of each country. The illustrations may include optional rather than standard fittings - consult your Case dealer. Furthermore, CNH reserves the right to modify machine specifications without incurring any obligation relating to such changes.

Conforms to directive 98/37/CE **CE**

